Inch

Slim Multi Recessed Light

- Interchangeable magnetic trims: white, black, silver, copper, chrome and brushed nickel
- Durable airtight aluminum body with iron trim
- Mounting: for use with a standard octagon junction box or 4" recessed housing
- I.C. rated for direct contact with insulation
- Suitable for WET LOCATION
- Rated for a long life over 50,000 hours



























Used for mounting to ground wire "O" style connector



Mounting Screws

Used when mounted to a fire-rated octagon iunction box



E26 base Adaptor

Used when mounted to a compatible 4" recessed housing



Butterfly mounting Clips With Screws


Used when mounted to a compatible 4" recessed housing


SPECIFICATIONS		
Application	Recessed Ceiling Mount	
Watts	8W	
CRI	90Ra+	
Color Temperature(K)	3000 K	
Light Ouput(Im)	500 lm	
Default Driver Input	AC120V, 60Hz	
Dimming	Triac Dimming	
Power Factor	>0.9	
Approved Location	Wet Location	
Air Tight	Yes	
Operating Temp.	(-4°F~104°F) -20~40°C	
Beam Angle	110°	

Ordering

MODEL	ССТ	FINISH
RF4-8W-3D-MW	Fixed CCT-3000K	MW (Matte White)
RF4-TRIM-MBK	Optional Trim	MBK (Matte Black)
RF4-TRIM-SLV	Optional Trim	SVL (Silver)
RF4-TRIM-BZ	Optional Trim	BZ (Bronze)
RF4S-TRIM-MW	Optional Square Trim	MW (Matte White)
RF4S-TRIM-MBK	Optional Square Trim	MBK (Matte Black)

Dimensions





Two ways to install

