


LED Regressed Downlight - Fixed

15 Light Micro Series


- Durable Aluminum body.
- Simple snap-in installation is fast and easy
- I.C. rated for direct contact with insulation
- No housing required
- Input voltage: AC 120V 60Hz
- 100-10% dimming capability this fixture is compatible with industry standard TRIAC/ELV dimmers
- Rated for a long life - over 50,000 hours
- Suitable for DAMP LOCATION



DIMMABLE DAMP LOCATION INSTANT ON/OFF



Cut Out: 10 3/4" X 1 1/2"



SPECIFICATIONS	
Application	Recessed Ceiling Mount
Light Output(lm)	750lm
Watts	30W
Optional Driver Input	Triac Dimming
CRI	80
Color Temperature(k)	3000K
Input Volts & Frequency	120V 60Hz
Approved Location	Damp Location
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	30°

Ordering

MODELS	CCT	FINISH
MR15L-30W-3D-30-MWB	3000K	MWB
MR15L-30W-4D-30-MWB	4000K	Matte White with
MR15L-30W-4D-15-MWB	4000K 15° Beam	Matte Black Insert

Accessories

Cover Plate



MR5-INSERT-MW

See Page 60

Mounting Plate



NR-7MULTI-NC

See Page 60

