


# LED Adjustable Down light

# 10 and 15 Light Adjustable

- Durable Aluminum body.
- Simple snap-in installation is fast and easy
- I.C. rated for direct contact with insulation
- Adjustable to 15°. No housing required
- Input voltage: AC 120V 60Hz
- 100-10% dimming capability this fixture is compatible with industry standard TRIAC/ELV dimmers
- Rated for a long life - over 50,000 hours
- Suitable for DAMP LOCATION



Cut Out: 10 3/4" X 1 1/2"



Cut Out: 16 3/4" X 1 1/2"

SPECIFICATIONS	
Application	Recessed Ceiling Mount
Light Output(lm)	<b>1500lm</b>
Watts	<b>20W</b>
Optional Driver Input	Triac Dimming
CRI	80
Color Temperature(k)	3000K
Input Volts & Frequency	120V 60Hz
Approved Location	Damp Location
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	30°

SPECIFICATIONS	
Application	Recessed Ceiling Mount
Light Output(lm)	<b>2400lm</b>
Watts	<b>30W</b>
Optional Driver Input	Triac Dimming
CRI	80
Color Temperature(k)	3000K
Input Volts & Frequency	120V 60Hz
Approved Location	Damp Location
Operating Temp.	(-4°F~104°F) -20~40°
Beam Angle	30°

## Ordering

MODELS	CCT	FINISH
MR10AL-20W-3D-30-MWB	3000K	MWB
MR10AL-20W-4D-30-MWB	4000K	
MR15AL-30W-3D-30-MWB	3000K	Matte White with
MR15AL-30W-4D-30-MWB	4000K	Matte Black insert

## Accessories

### Cover Plate



MR5-INSERT-MW

See Page 60