


Round LED Surface Mount Down Light



12", 22 watts Round LED Surface Mount Down Light is a low-profile down light intended for ceiling mount applications.



Includes

- (1) Surface mount fixture
- (1) Mounting plate
- (3) Wire Nuts
- (1) Fitting instruction
- (2) Wood screws
- *Specifications and dimensions subject to change without notice.

Features

- Driver on Board Technology, provides a 120V alternating current source and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- · Die-cast aluminum housing
- Smooth and continuous dimming, dimmable with most standard dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- · cETLus listed for wet locations
- 5 year limited warranty are powder coat painted and available in the following finishes: White Gloss Enamel (WH), Bronze (BZ), Brushed Nickel (BN) and Black (BK)

Specifications				
Electrical	Input: AC 100 – 120V 22W			
Power Factor	0.95			
LEDs	Epistar			
LED Life	50,000 hours			
Lumen Output WW = Warm White NW = Neutral White	1800 WW, 1850 NW			
Lumen Efficacy (LPW) WW = Warm White NW = Neutral White	82 WW, 84 NW			
Color Temperature	Warm White 3000K Neutral White 4000K			
CRI	≥80			
Appearance Size (D x H)	12" x 1" (305mm x 25mm)			
Approvals	cETLus listed for wet locations, Energy Star rated			

Ordering Code

LED Color Trim Finish

LVLDL - SR - 12 - WW = Warm White WH = White (3000K) BK = Black NW = Neutral White BZ = Bronze (4000K) BN = Brushed Nickel

Project	Туре	
Date	Contact	
Notos		









