


# **LED Neon Flex**



LED Neon Flex is a functional, flexible option to highlight architectural and design elements while adding color and vibrancy to building exteriors.





#### **Features**

- ✓ Virtually maintenance free
- ✓ Low power consumption
- ✓ Maximum length 40FT (12.2M)
- ✓ Safe 24V DC operation
- ✓ cETLus certified
- ✓ Dimmable
- ✓ Inter-connectable
- ✓ Field cuttable (every 4" single color, every 12" RGB)
- ✓ Custom cuts available
- ✓ Available in seven brilliant colors, and RGB
- ✓ Highly flexible, with neon look
- ✓ Indoor/outdoor use
- √ 30,000 hour life
- √ 3 year limited warranty

## **Applications**

- Building outlines
- Stairway and aisle lighting
- Signs
- Decks
- Pathway lighting
- Billboards
- Highlighting architectural features



## **LED Neon Flex**

LED dimmable technology in flexible, vibrant strip lighting.

#### **Colors**

WW = 3000K + /-200K, NW = 4000K + /-200K, CW = 6000K + /-200K, RD = Red, GR = Green, BL = Blue, AM = Amber, RGB

#### **Electrical**


24V DC, 2.44W/FT (8W/M)

#### Certification

cETLus listed for indoor and outdoor applications including wet locations.

#### **Warranty**

**Limited warranty:** This fixture is free from defects in materials and workmanship for a period of 3 years from date of purchase.





### **Specifications**

|                       | LED Neon Flex   |
|-----------------------|---|
| Product Code          | NFLX-XX-YY  |
| Color Temperature     | WW = 3000K +/- 200K<br>NW = 4000K +/- 200K<br>CW = 6000K +/- 200K<br>RD = Red<br>GR = Green<br>BL = Blue<br>AM = Amber<br>RGB |
| Electrical            | 24V DC, 2.44 W/FT (8W/M)  |
| Lumen Output          | 61 LM/FT (200LM/M)  |
| Efficacy              | 25 LPW  |
| Custom Cuttable       | 4" single color, 12" RGB  |
| Maximum length        | 40FT (12.2M)  |
| LED Life (hours)      | 30,000  |
| Beam angle            | 120°  |
| Color Rendering Index | >80   |
| Dimmable              | Yes   |
| Approvals             | cETLus  |

XX= length YY= color

#### SINGLE COLOR ACCESSORIES

NFLX-CONKIT-6FT



(Power feed connector, 6FT) (Jumper connector, 15CM [6in]) (Single color pins)

NFLX-PINS







NFLX-SPLICE (In-line splice connector)

NFLX-L-SPLICE (L splice connector)

NFLX-T-SPLICE (T splice connector)







NFLX-ENDS (End cap)

NFLX-CLIPS (Mounting clips)

**NFLX-CHANNEL** (Aluminum mounting channel 1M [3.28FT])







#### RGB ACCESSORIES

(RGB controller)

NFLX-RGB-CONTROL NFLX-RGB-AMP (RGB signal amplifier) NFLX-RGB-CONKIT-6FT (RGB power feed connector,









NFLX-RGB-CONKIT-6FT-O (RGB power feed connector, 6FT, opposite)

NFLX-RGB-JUMP (RGB Jumper connector 15cm [6in])



**NFLX-RGB-PINS** (RGB pins)





(End cap)







**NFLX-CLIPS** (Mounting clips)

NFLX-CHANNEL (Aluminum mounting channel 1M [3.28FT])







