


RGB LED eStrip

RGB eSTRIP utilizes RGB LEDs allowing you to produce dramatic color change effects for building outlines, architectural features or anywhere eye catching color changing display lighting is needed.



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 year limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

PRODUCT CODES


40Ft spools
LES - 40 - RGB

Custom cuts
LES - XX - RGB

NOTE: Sold in 2ft. increments

SPECIFICATIONS

Electrical	24V DC, 2.2W/ft
Viewing Angle	120°
LED Life	40,000 hours
LED Spacing	1.3" (33mm)
Maximum Length	40' (12m)
Custom Cuttable	8" (198mm)
LED Colors	RGB
Min/Max Surface Temperature for Mounting	-40°C - 40°C (-40°F - 104°F)
PVC Body Color	Clear
Dimensions	.3" X .6" (7.6mm x 15mm)
Approvals	cETLus



ACCESSORIES

LES-BTFN
Female connector

LES-BTMN
Male connector

LES-BTSN
In line connector

LES-BTMCJ-1.5
1.5' Power connector

LES-BTMCJ-6
6' Power connector

LES-BTMC-G4-SI
Signal in connector for RGB eStrip connection to outdoor signal amplifier

LES-BTMC-G4-SO
Signal out connector for RGB eStrip connection to outdoor signal amplifier

LES-001-OD-6FT
Power feed connector for connection to outdoor signal amplifier

LES-STCN
Cutting end cap

LES-STFN
Female end cap

LES-STPV-T
Clear PVC mounting "U" channel (1M)

LES-SNPT
Wood nail clips, 1/4" X 1/2" (6mm x 12mm)

LES-C-6
Tie wrap

LES-MX-1
Allen key

TCJ-E06
6' (1.8m) Extension cord
TCJ-E30
30' (9.1m) Extension cord

LES-TCJ-EI6-N
LED RGB eStrip 6" Flex Connector

LT-09S-RF
6 Key RGB "touch" controller 12/24V DC

LN-CON-WIFI-3CH-XV
WiFi controller for RGB, c/w RF remote 12/24VDC

LV-ZJFFS-3CH-6INW
Outdoor RGB signal amplifier

NON DIMMABLE DRIVERS

LEDDR-24-120W
Indoor/Outdoor driver
Max 40' (12.1m) per single tap
Max 54' (16.46m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)